



Model: LP301730HA		Overcharge Detection Voltage(V)	4.28±0.05
Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)		Overdischarge Detection Voltage(V)	3.0±0.1
95		过放保护电压 (V)	Limited to Max loading current
Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)		仅用于最大的负载电流 peak value (A)	constant (A) 持续 0.5 (A)
100		客户要求最大的负载电流 peak value (A)	constant (A) 持续 (A)
Nominal Voltage 标称电压 (V)		Customer required Max loading current 峰值 (A)	持续 (A)
3.7		Battery protection (相关的电芯保护值)	
Internal impedance 内阻 (≦) (m ,AC 1KHz)		If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appro- priate PCM design. (如果实际应用的负载电流大于 EEMB 提供值, 请提出来, 实际的应用 情况对 PCM 的设计至关重要)	
500		Ambient Conditions (环境温度)	
Charge Temp. 充电温度 (°C)		0~45	
Discharge Temp. 放电温度 (°C)		-20~60	
Humidity(湿度)		65±20%	

EEMB BATTERY		Drawn:	-eiyuanhao	Revise No.:	E4-2009
Title	LP301730HA-PCM-LD	Checked 1:	Catherine	Projection:	
File NO.	A13207	Checked 2:		Page:	1/1
		Approved:		Scale:	1 : 1.5
		Draw Date:	2016/09/14	Unit:	mm

Remark(备注):

1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
2. Rohs compliant(严格按照ROHS要求生产)
3. Thickness Of PCM Area ≦ 3.3mm. The edgefold's thickness ≦ 3.5mm(顶部保护板区域 ≦ 3.3mm, 折边区厚度 ≦ 3.5mm)