



Model: LP404261		Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	950	Overcharge Detection Voltage (V)	4.28±0.05
Battery pack specification 电池组规格		Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	1000	Overdischarge Detection Voltage (V)	2.3±0.1
		Nominal Voltage 标称电压 (V)	3.7	Limited to Max loading current 仅用于最大的负载电流 peak value (A)	constant (A) 持续 2.0 (A)
		Internal impedance 内阻 (≦) (mΩ, AC 1KHz)	200	Customer required Max loading current 客户要求最大的负载电流 peak value (A)	constant (A) 持续 (A)
Ambient Conditions (环境温度)		Charge Temp. 充电温度 (°C)	0~45	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如实际应用的负载电流大于 EEMB 提供值, 请提出来, 实际的应用情况对 PCM 的设计至关重要)	
		Discharge Temp. 放电温度 (°C)	-20~60		
		Humidity (湿度)	65±20%		

EEMB BATTERY		Drawn: Yanf	Revise No.: E4-2009
Title	LP404261-PCM-LD	Group: Group37	Projection:
File NO.	A16831	Approved1:	Page: 1/1
		Draw Date: 2019/03/08	Scale: 1:1
			Unit: mm

Remark(备注):
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. RoHS compliant(严格按照ROHS要求生产).