



Model: LP461745		Overcharge Detection Voltage(V)	4.28±0.05
Battery pack specification (电池组规格)	Min.Capacity 最低容量(mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)	过充保护电压(V)	3.0±0.1
	Typical Capacity 典型容量(mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)	过放电保护电压(V)	
	Nominal Voltage 标称电压(V)	Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 1.0 (A)	constant (A) 持续 0.5 (A)
Internal impedance 内阻(≅) (mΩ,AC 1KHz)	3.7	Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 (A)	constant (A) 持续 (A)
Charge Temp. 充电温度(°C)	0~45	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	
Discharge Temp. 放电温度(°C)	-20~60		
Humidity(湿度)	65±20%		

Battery protection
Related Value:
(相关的电池保护值)

Remark(备注):
1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
2. Rohs compliant(严格按照ROHS要求生产).

		Drawn:	Sophie	Revise No.:	E4-2009
		Checked 1:	Rachel	Projection:	
Title	LP461745-PCM-LD	Checked 2:		Page:	1/1
File NO.	A09212	Approved:		Scale:	1 : 1
		Draw Date:	2014/02/15	Unit:	mm