



PQ型/PQ CORE

型号 TYPE	尺寸 Dimensions (mm)						
	A	B	C	D	E	F	G
PQ20/7	21.25±0.4	18.0±0.4	8.8±0.2	14.0±0.4	1.32±0.1	3.53 ⁺⁰ _{-0.1}	12.0min
PQ20/10	20.5±0.4	18.0±0.4	8.8±0.2	14.0±0.4	2.65±0.1	4.9±0.1	12.0min
PQ20/11	20.5±0.4	18.0±0.4	8.8±0.2	14.0±0.4	2.65 ^{+0.3} ₋₀	5.4 ^{+0.2} ₋₀	12.0min
PQ20/12	20.5±0.4	18.0±0.4	8.8±0.2	14.0±0.4	3.05±0.15	6.0±0.1	12.0min
PQ20/16	20.5±0.4	18.0±0.4	8.8±0.2	14.0±0.4	5.0 ^{+0.3} ₋₀	8.0 ^{+0.2} ₋₀	12.0min
PQ20/17	20.5±0.4	18.0±0.4	8.8±0.2	14.0±0.4	5.5 ^{+0.2} ₋₀	8.5 ^{+0.2} ₋₀	12.0min
PQ20/20	20.9±0.8	18.0±0.4	8.8±0.2	14.0±0.4	7.25±0.25	10.1±0.1	12.0min
PQ20/20A	21.3±0.4	18.0±0.4	8.8±0.2	14.0±0.4	7.15 ^{+0.3} ₋₀	10.1 ^{+0.15} _{-0.5}	12.0min
PQ26/11	26.5±0.45	22.5±0.45	12.0±0.2	19.0±0.45	2.65 ^{+0.3} ₋₀	5.4 ^{+0.2} ₋₀	15.5min
PQ26/14	26.95 ⁺⁰ _{-0.9}	22.05min	12.2 ⁺⁰ _{-0.4}	19.45 ⁺⁰ _{-0.9}	2.5±0.1	7.0 ⁺⁰ _{-0.2}	15.5min
PQ26/17	26.95 ⁺⁰ _{-0.9}	22.4min	12.2 ⁺⁰ _{-0.4}	19.45 ⁺⁰ _{-0.9}	3.9 ^{+0.2} ₋₀	8.45 ⁺⁰ _{-0.2}	15.5min
PQ26/18	26.5±0.45	22.5±0.45	12.2 ⁺⁰ _{-0.4}	19.0±0.45	4.3 ^{+0.3} ₋₀	9.0 ⁺⁰ _{-0.25}	15.5min
PQ26/20	26.5±0.45	22.5±0.45	12.0±0.2	19.0±0.45	5.75±0.15	9.95 ^{+0.25} ₋₀	15.5min
PQ26/20A	26.5±0.45	22.5±0.45	12.0±0.3	19.0±0.45	6.2±0.2	10.45±0.2	15.5min
PQ26/20B	26.5±0.45	22.5±0.45	12.0±0.2	19.0±0.45	5.75 ^{+0.3} ₋₀	10.2 ^{+0.1} _{-0.25}	15.5min
PQ26/22	26.5±0.45	22.5±0.3	12.0±0.2	19.0±0.3	7.2±0.2	11.45±0.2	
PQ26/25	26.5±0.45	22.5±0.45	12.0±0.2	19.0±0.45	8.1±0.2	12.5 ^{+0.25} ₋₀	15.5min
PQ32/16	32.0±0.5	27.5±0.5	13.45±0.25	22.0±0.5	3.4 ^{+0.3} ₋₀	8.05 ⁺⁰ _{-0.18}	19.0min
PQ32/18	32.5 ⁺⁰ _{-1.0}	27.0 ^{+1.0} ₋₀	13.7 ⁺⁰ _{-0.5}	22.5 ⁺⁰ _{-1.0}	4.5 ^{+0.3} ₋₀	9.0 ⁺⁰ _{-0.25}	19.0min
PQ32/19	32.5 ⁺⁰ _{-1.0}	27.0 ^{+1.0} ₋₀	13.4±0.3	22.5 ⁺⁰ _{-1.0}	5.05 ^{+0.3} ₋₀	9.55 ^{+0.3} ₋₀	19.0min
PQ32/20	32.0±0.5	27.5±0.5	13.4±0.3	22.0±0.5	5.75±0.15	10.25±0.15	19.0min
PQ32/21	32.0±0.5	27.5±0.5	13.45±0.25	22.0±0.5	5.95±0.2	10.475±0.2	19.0min
PQ32/24	32.5 ⁺⁰ _{-1.0}	27.0 ^{+1.0} ₋₀	13.7 ⁺⁰ _{-0.5}	22.5 ⁺⁰ _{-1.0}	7.2 ^{+0.3} ₋₀	12.0 ⁺⁰ _{-0.25}	19.0min
PQ32/25	32.0±0.5	27.5 ^{+0.5} _{-0.2}	13.45±0.25	22.0±0.5	8.25±0.15	12.35±0.15	19.75min

PQ型/PQ CORE

型号 TYPE	C1 (mm ⁻¹)	Ae (mm ²)	Amin (mm ²)	Le (mm)	Ve (mm ³)	AL±25%(nH/N2)			重量(g)
						TP4	TP4A	TP4W	Weight
PQ20/7	0.38	54.5	43.9	20.7	1132	4050	4220	4800	5.8
PQ20/10	0.47	54.7	45.1	26.1	1426	3750	3750	4310	7.3
PQ20/11	0.47	58.9	54.1	27.6	1628	3800	3830	4220	9.6
PQ20/12	0.50	59.6	59.1	29.3	1743	3670	3670	4260	9.0
PQ20/16	0.60	62.0	56.1	37.4	2310	3400	3430	3890	12.9
PQ20/17	0.61	62.0	60.1	37.4	2430	3150	3430	3830	14.4
PQ20/20	0.74	61.4	57.1	45.4	2790	2740	2830	3360	14.3
PQ20/20A	0.72	62.6	53.4	45.5	2850	2900	2900	3450	14.6
PQ26/11	0.29	110.1	74.1	32.4	3567	6560	6560	7640	18.3
PQ26/14	0.30	120.5	113.1	32.0	3859	6120	6310	7350	22.3
PQ26/17	0.31	121.6	131.1	37.5	4560	4600	4700	7540	27.5
PQ26/18	0.33	120.6	131.1	39.8	4804	5940	6140	7230	26.8
PQ26/20	0.37	120.1	131.1	44.7	5372	5510	5650	6690	28.2
PQ26/20A	0.39	119.0	131.1	46.3	5546	5250	5410	6420	28.5
PQ26/20B	0.37	121.0	131.1	45.0	5445	5510	5660	6700	28.0
PQ26/22	0.42	119.6	131.1	50.3	6026	4800	5120	6100	31.0
PQ26/25	0.44	121.4	131.1	54.3	6605	4670	4980	5950	33.9
PQ32/16	0.27	163.3	137.6	44.1	7205	7460	8650	9130	37.0
PQ32/18	0.30	159.9	131.8	48.3	7735	6860	7100	9450	41.7
PQ32/19	0.31	162.6	140.1	50.9	8276	6500	6500	8300	40.8
PQ32/20	0.33	163.6	140.1	53.7	8791	6390	6620	7910	45.2
PQ32/21	0.32	170.0	141.2	55.5	9435	5800	6880	8230	48.5
PQ32/24	0.37	164.5	141.2	60.9	10023	5850	6070	7290	51.5
PQ32/25	0.40	158.6	127.7	64.2	10178	5400	5400	6830	52.3

PQ型/PQ CORE

型号 TYPE	图例 FIG.	尺寸 Dimensions (mm)						
		A	B	C	D	E	F	G
PQ32/25A	1	32.0±0.5	27.5±0.5	13.4±0.3	22.0±0.5	8.2±0.2	12.45±0.2	19.0min
PQ32/28	1	32.0±0.5	27.5±0.5	13.45±0.25	22.0±0.5	9.65±0.2	14.0±0.2	19.0min
PQ32/30	1	32.0±0.5	27.5±0.5	13.45±0.25	22.0±0.5	10.5 ^{+0.3} ₋₀	15.3 ⁺⁰ _{-0.3}	19.0min
PQ32/32	1	32.0±0.5	27.5±0.5	13.0±0.3	22.0±0.5	11.5 ^{+0.3} ₋₀	16.15±0.15	19.0min
PQ32/35	1	32.0 ^{+0.7} _{-0.5}	27.5±0.5	13.45±0.25	22.0±0.5	13.25±0.15	17.75±0.125	19.5min
		H:4.5±0.15	l:2.25±0.2					
PQ33/21	1	33.0±0.5	27.5±0.5	13.5±0.25	22.0±0.5	5.75±0.15	10.3±0.125	19.0min
PQ35/23	1	35.1±0.6	32.0±0.5	14.35±0.25	26.0±0.5	7.0min	11.55±0.15	23.5min
		H:1.4±0.15	l:4.4±0.15					
PQ35/35	1	35.1±0.6	32.0±0.5	14.35±0.25	26.0±0.5	12.5±0.25	17.5 ⁺⁰ _{-0.25}	23.5min
PQ40/29	1	40.0 ^{+1.4} _{-0.4}	36.4min	15.0 ⁺⁰ _{-0.6}	28.0 ^{+0.45} _{-0.6}	9.18±0.15	14.33±0.15	27.2min
PQ40/40	1	40.0 ^{+1.4} _{-0.4}	37.0±0.6	15.0 ⁺⁰ _{-0.6}	28.0 ^{+0.45} _{-0.6}	14.6 ^{+0.3} ₋₀	20.0 ⁺⁰ _{-0.25}	27.2min
		H:5.15±0.15	l:1.75±0.15					
PQ50/35	1	50.0±0.7	44.0±0.7	20.0±0.35	32.0±0.6	10.55±0.3	17.5±0.25	32.0min
PQ50/50	1	50.0±0.7	44.0±0.7	20.0±0.35	32.0±0.6	18.1±0.25	25.0±0.15	32.6±0.6

PQ型/PQ CORE

型号 TYPE	C1 (mm ⁻¹)	Ae (mm ²)	Amin (mm ²)	Le (mm)	Ve (mm ³)	AL±25%(nH/N ²)			重量(g)
						TP4	TP4A	TP4W	Weight
PQ32/25A	0.37	161.2	132.3	60.6	9765	5400	6060	7280	50.2
PQ32/28	0.42	166.8	135.7	69.9	11656	5300	5490	6630	59.9
PQ32/30	0.46	161.0	140.4	74.6	12000	5070	5070	6140	61.6
PQ32/32	0.48	162.2	132.7	78.6	12765	4720	4900	5950	65.6
PQ32/35	0.50	169.0	140.6	85.9	14541	4780	4780	5810	74.68
PQ33/21	0.31	171.2	143.1	53.7	9211	6000	6000	8400	47.3
PQ35/23	0.35	179.0	148.7	63.1	11299	5000	6460	7770	58.03
PQ35/35	0.45	196.0	161.7	87.9	17300	4800	5320	6480	88.9
PQ40/29	0.40	199.0	169.7	79.0	15744	5670	6000	7150	80.9
PQ40/40	0.50	201.0	169.7	101.9	20500	4300	4890	5990	105.29
PQ50/35	0.28	328.0	314.2	92.7	30400	8300	8800	10520	156.1
PQ50/50	0.36	320.0	314.2	114.6	36674	6720	6900	8470	188.4